

# - PRODUCT DATA SHEET SEO7R







2 - PRODUCT DATA SHEET V230803

### SEO7R

### PRODUCT DESCRIPTION

The SEO7R has everything that you could wish for in a modern headlamp.  $220 \, \mathrm{lm}^1$  strong with a  $130 \, \mathrm{m}^1$  lighting range. The Optisense technology (dimming function) ensures an automatic adjustment to the lighting conditions. It can also run on rechargeable or on normal batteries. That makes sense, right?

- Simple to charge Using USB charging cable
- Infinite regulation of the light intensity according to activity Thanks to the integrated Optisense Technology the reflected light is measured in real time
- Individual headlamp adaptation to the current usage situation Smart Light Technology
- From the homogeneous circle of close range lighting (defocused) to a sharply bundled long-distance beam (focused) – The patented<sup>3</sup> Advanced Focus System with reflector lense enables efficient, tailored lighting
- Glare-free red light Good for reading documents



| TECHNICAL DATA                              |                        |
|---------------------------------------------|------------------------|
| Head diameter [mm]                          | 29                     |
| Weight incl. batteries [g]                  | 93                     |
| Weight without batteries [g]                | 71                     |
| Focus function                              | Yes                    |
| Head material                               | PC                     |
| Tube material                               | PC                     |
| Optic                                       | Plastic lense (PMMA)   |
| Headband material                           | Elastic fabric         |
| Headband type                               | Side headband          |
|                                             | Side Headballd         |
| Head movement type                          | Stepless movement      |
|                                             | 0.000000               |
| Head movement type                          | Stepless movement      |
| Head movement type  Head movement angle [°] | Stepless movement 41.5 |

| POWER SUPPLY                           |                                          |
|----------------------------------------|------------------------------------------|
| Power source type                      | Rechargeable battery                     |
| Battery quantity                       | 1                                        |
| Battery type                           | Li-ion                                   |
| Battery replaceable                    | Yes                                      |
| Total battery voltage [V]              | 3.7                                      |
| Total battery capacity [mAh]           | 880                                      |
| Total battery energy <sup>2</sup> [Wh] | 3.256                                    |
| Rechargeable                           | Yes                                      |
| Charging time <sup>5</sup> [min]       | 240                                      |
| Energy modes                           | Constant Current,<br>Energy Saving       |
| Energy status indicator                | Charge Indicator,<br>Low Battery Warning |
| Usable batteries                       | AAA Alkaline 1.5V,<br>AAA NiMH 1.2V      |

| FURTHER SPECIFICATION          | INS        |
|--------------------------------|------------|
| IP class                       | IPX6       |
| Drop test (drop height) [m]    | 1.5        |
| Working temperature range [°C] | -20 to +40 |

#### LIGHT FUNCTIONS

Low Power, Power, Blink

| LIGHT SOURCE                |              |
|-----------------------------|--------------|
| Amount LEDs                 | 1            |
| LED type                    | Power LED    |
| Color                       | White        |
| Color temperature [K]       | 6000 to 8000 |
| Color rendering index (CRI) | 70           |

| LIGHT VALUES                   | 5     |       |                     |
|--------------------------------|-------|-------|---------------------|
| ANSI – Energy Saving           | Boost | Power | Mid Power Low Power |
| Light output <sup>1</sup> [lm] |       | 220   | 20                  |
| Beam distance <sup>1</sup> [m] |       | 130   | 40                  |
| Run time <sup>1</sup> [h]      |       | 5     | 20                  |

#### **SWITCH**

Front Switch

#### FEATURES

Transportation lock , Dimmable , Red reading light

#### **TECHNOLOGIES**

Advanced Focus System³, Optisense Technology, Rapid Focus, Smart Light Technology, Temperature Control System, Dual Power Source



3 - PRODUCT DATA SHEET

# SE07R

### PACKAGING AND LOGISTICS



**Exemplary Packaging Illustration** 

| PACKAGING INFORMATION |                                               |  |
|-----------------------|-----------------------------------------------|--|
| Type of packaging     | Box                                           |  |
| Scope of delivery     | 1 set of rechargeable batteries,<br>USB cable |  |
| Item No.              | 6007-RB                                       |  |
| Customs tariff number | 85131000000                                   |  |
| Color                 | black                                         |  |

| SINGLE PACKAGE            |                   |
|---------------------------|-------------------|
| Dimensions W x H x D [cm] | 10.1 x 10.3 x 9.4 |
| Gross weight [g]          | 216               |
| GTIN-13                   | 4029113600736     |

| INNER CARTON              |                  |
|---------------------------|------------------|
| Unit                      | 12               |
| Dimensions W x D x H [cm] | 30 x 21.2 x 21.5 |
| Gross weight [g]          | 2716             |
| GTIN-13                   | 4029113600743    |

| <b>EXPORT CARTON</b>      |                    |
|---------------------------|--------------------|
| Unit                      | 24                 |
| Dimensions W x D x H [cm] | 46.5 x 33.5 x 25.5 |
| Gross weight [kg]         | 6.3                |
| GTIN-13                   | 4029113600750      |



5 - PRODUCT DATA SHEET v230803

# SE07R

### **ACCESORIES**

| PRODUCT CATEGORY      | ITEM NUMBER | PRODUCT NAME                             |  |
|-----------------------|-------------|------------------------------------------|--|
| Fastenings / Brackets | 0368        | Helmet Connecting Kit Type B             |  |
| Charger / Cable       | 0380        | USB Car Charger                          |  |
| Charger / Cable       | 0389        | USB Power Supply and Adapter Cable       |  |
| Fastenings / Brackets | 0390        | Rubberized Reflecting Helmetband         |  |
| Battery               | 7784        | Li-Ion rechargeable Battery pack 880 mAh |  |
| Fastenings / Brackets | 500935      | Reflective Chest Belt Type A             |  |
| Battery               | 500981      | 4x AAA Alkaline Ionic                    |  |



6 - PRODUCT DATA SHEET v230803

### SEO7R

### PRODUCT SERIES

The Headlamps of the Ledlenser SEO-Series As unique as those who wear them.

Fresh colors, cool design and excellent luminosity - these are the headlamps of the Ledlenser SEO-Series. In addition, they are easy to use and light-weight, and have innovative functions, such as the Ledlenser SEO7R's automatic fade out function. There are colors and features to suit everyone. And last but not least, reasonable prices.

### **FOOTNOTES**

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/hrs/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

- 2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.
- 3) EP Patent 1880139, US Patent 7,461,960
- 4) Warranty period of five years from the date of purchase, seven years if the product is registered online on our website. The warranty is valid worldwide and legal warranty rights also apply. It covers defects in materials and workmanship. For the proper functioning of rechargeable batteries a different warranty period of 24 months applies. Excluded from this warranty are the product series "Solidline", Ledlenser K1 and Ledlenser K2. The warranty does not apply to Defects in batteries, holsters, pouches, remote switches, color filters, imprints or surface coatings. The guarantor is Ledlenser GmbH & Co. KG, Kronenstr. 5 7, 42699 Solingen, Germany. More information: ledlenser.com/warranty
- 5) Charging time varies by hardware used.

