



— PRODUCT DATA SHEET

TX3R



TX3R

PRODUCT DESCRIPTION

The Chip Fire TX3R, powered by a rechargeable 18650 Li-ion battery, is ideal for those looking for a powerful and compact flashlight. It delivers high performance with 1000 lumens of brightness and a range of 230 meters.

- Designed for tactical operations, offering a combination of flood and spotlight with brightness of up to 1000 lm.(Focus System)
- Easy to use: 3-step mode with a transport lock.
- Light modes: high, medium, low, strobe (blinking).
- Extremely durable: hard-anodized aluminum housing with high resistance to water and dust (IP54).
- Powerful 18650 Li-Ion battery, rechargeable via the battery (charging cable not included).

TECHNICAL DATA	
Weight incl. batteries [g]	144
Material	Aluminum alloy
Length [mm]	140
Tube diameter [mm]	22
Head diameter [mm]	29

POWER SUPPLY	
Battery quantity	1
Rechargeable	Yes
Battery type	Lithium-ion
Total battery voltage [V]	3.6
Total battery capacity [mAh]	2500
Total battery energy [Wh]	9 Wh
Battery replaceable	Yes
Charging time [min]	210
Energy status indicator	Battery Indicator, Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS			
IP class	IP54		
Drop test (drop height) [m]	2		
Working temperature range [°C]	-20 to +40		

LIGHT FUNCTIONS			
Cool White Main: Power, Low power, Strobe			

LIGHT SOURCE	MAIN	ALTERNATE	ALTERNATE
Amount LEDs	1		1
Color	Cool White		
Color temperature [K]	6000 to 7500	-	-
Color rendering index (CRI)	70	-	-

TX3R

LIGHT VALUES - Cool White Main

	Power	Mid power	Low power
Light output [lm]	1000		15
Beam distance [m]	230		25
Run time [h]	3		45

LIGHT VALUES - Red Alternate

	Power
Light output [lm]	
Beam distance [m]	-
Run time [h]	-

LIGHT VALUES - Blue Alternate

Power
Light output [lm]
Beam distance [m]
Run time [h]

SWITCH

End-cap Multifunctional switch,

FEATURES

TECHNOLOGIES

Temperature Control System

TX3R

PACKAGING AND LOGISTICS



PACKAGING INFORMATION

Type of packaging	Peg
Scope of delivery	Pouch Type G, Adjustable Lanyard
Item No.	502033
Color	Black
MSRP price (€)	59

SINGLE PACKAGE

Dimensions W x H x D [cm]	11 x 21 x 4,5
Gross weight [g]	250
GTIN-13	4058205019088

EXPORT CARTON

Unit	24
Dimensions W x H x D [cm]	
Gross weight [g]	
GTIN-13	

TX3R

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

*) 7 year warranty only if registered, otherwise 2 years.
Warranty conditions viewable at <https://ledlenser.com/en/infos-service/warranty/>

1) Measured values according to ANSI/PLATO FL 1 in the respective setting named. If no setting is specifically named, the luminous flux (lumens/lm) and range (meters/

m) values refer to the brightest setting and the burn time (hours/h) values refer to the lowest setting. A boost function (if available) can be used several times, but is only available for a short time at a time. In case the lamp is equipped with colored LED(s), the measured values are given with white light or the white LED. If the lamp has different energy modes, the "energy saving mode" is the basis for the measurement.

2) Calculated value of the capacity in watt-hours (Wh). This applies to the battery(ies) contained in the delivery condition of the respective item or, in the case of lamps with rechargeable battery, to the battery(ies) contained herein in a fully charged condition.